TECHNICAL DATA SHEET



ASPHALT & TAR REMOVER DE-776

Asphalt & Tar Remover DE-776 is a specifically formulated detergent used for removal of tar, asphalt, tree sap, adhesive residues, oil field tars and greases. This product is able to be flushed away with water. For use on asphalt/tar trucks, oil field equipment, heavy duty road equipment, painted and plastic surfaces. Easily applied with spray or brush. To use, allow the detergent to sit and penetrate then flush with high pressure rinse.

Product Highlights

- Formulated with biodegradable surfactants, petroleum distillates and citrus by-products.
- ♦ Economical per gallon cost.
- DE-776 can be diluted with up to 3 parts of diesel fuel. Many asphalt paving companies love the heavy duty, quick acting performance on the heaviest of build-up.
- DE-776 is a non-corrosive product that makes it environmentally friendly and provides maximum user and equipment safety.
- DE-776 will float on water. Collect and investigate as a fuel in a waste oil furnace. This can eliminate expensive disposal costs and any potential hazardous wastewater. This product can be removed with an oily water separator or skimmed off the surface of a holding reservoir. Works well in hard or soft water.
- Non-Hazardous Fully Biodegradable, NO chlorinated solvents.
- ♦ Does not carry ingredients that attack the earth's ozone, or contribute to smog.

Physical Description

- ♦ 100% Active Ingredients
- ♦ Flash point = > 121°F
- ♦ pH 5% Solution = 6-9
- Specific Gravity = 0.82
- ♦ VOC = 779 g/L
- Does ship UPS
- Shelf Life = 2 years
- Freeze / thaw stable
- Appearance = Clear

Application Directions:

Apply directly to the surface. Allow to dissolve tar, asphalt and/or other soil. Make sure you rinse thoroughly with cool, clear, potable water after cleaning.

Available in

20 L Pail ◆ 205 L Drum ◆ 1000 L Tote

HI PRESSURE EQUIPMENT

#125 – 12051 Horseshoe Way, Richmond, B.C V7A 4V4 604-940-1599 www.hipequip.com